

VM-10LCD

speco technologies®

10.4" TFT Color LCD Monitor



rear of unit

VM-10LCD

Features

- Professional TFT LCD for surveillance with multiple connections
- Compatible with VGA (640X480)
- Picture-In-Picture feature that allows multi-picture display (in VGA mode)
- High brightness level and contrast ratio with super wide viewing angle
- Built-in 3D comb filter and 3D de-interlace for display picture performance
- Fast response time and refresh rate
- Provides 6500K and 9300K color temperature selection for user's preference
- Provides Key Lock and power memory function for easy management
- CCD mode control auto-adjusts incoming video signal level
- Video looping output supports 75 ohm auto termination
- Audio and live-out function with stereo phone jack output
- Remote Controller included
- Video inputs support NTSC / PAL standards
- VESA standards bracket compatibility (75mm x 75mm)

Specifications

Panel Size	10.4"
Aspect Ratio	4:3
Resolution / Scan	640 x 480
Brightness	350cd/m2
Contract Ratio	300:1
Viewing Angle(H/V)	Left 70°/ Right 70° / Up 40° / Down 70°
Response Time	6ms (Typ)
Sync. Format	NTSC / PAL
Frequency (Horizontal)	PC: 31.5K
Frequency (Vertical)	PC: 60Hz -75Hz, Video: 50 / 60Hz
Video Interface	D-SUB 15IN x 1, Video In x 2 (BNC), Video Out x 2 (BNC), S-Video In x 1
Audio Interface	Audio In x 2, Audio Out x 2, PC-Audio In x 1
Input Power	DC In x 1
Termination	75 ohm (Auto Termination)
Built-in Speakers	Yes (2pcs)
Front Panel Button	Power, Source, Up, Down, Menu, Auto
OSD Language	Multi Language
VESA Mounting	VESA 75mm x 75mm
Weight (N.W./G.W.)	4 lbs. / 6.4 lbs.
External Dimensions	10.3" W x 8.8" H x 2.5" D
Power	12V DC
Power Consumption (max)	17.2 W
Temp (Oper.)	-10°C to 50°C (14°F ~ 122°F)
Humidity	20% ~ 80%
Accessories (included)	Power cord, User Manual, Remote Control

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
 Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880